

## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>ADVANCED ENVIRONMENTAL RECYCLING TECHNOLOGIES, INC.</b>	
8110-2040:0001	<p><b>Company:</b> ADVANCED ENVIRONMENTAL RECYCLING TECHNOLOGIES, INC.  <b>Address:</b> 914 North Jefferson, Springdale, AR 72764  <b>Contact:</b> John Dempsey  <b>Phone:</b> (479) 203-5062 <b>Fax:</b> (479) 756-7410  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "ChoiceDek® FR" composite wood plastic deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2040:0002	<p><b>Company:</b> ADVANCED ENVIRONMENTAL RECYCLING TECHNOLOGIES, INC.  <b>Address:</b> 914 North Jefferson, Springdale, AR 72764  <b>Contact:</b> John Dempsey  <b>Phone:</b> (479) 203-5062 <b>Fax:</b> (479) 756-7410  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "MoistureShield® FR" composite wood plastic deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Tamko Building Products, Inc.</b>	
8110-2044:0001	<p><b>Company:</b> Tamko Building Products, Inc.  <b>Address:</b> 220 West 4th Street, Joplin, MO 64801  <b>Contact:</b> Aaron Phillips  <b>Phone:</b> (417) 624-6644 <b>Fax:</b> (800) 841-1925  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "EverGrain" composite deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2044:0002	<p><b>Company:</b> Tamko Building Products, Inc.  <b>Address:</b> 220 West 4th Street, Joplin, MO 64801  <b>Contact:</b> Aaron Phillips  <b>Phone:</b> (417) 624-6644 <b>Fax:</b> (800) 841-1925  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "EverGrain" composite deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2044:0003	<p><b>Company:</b> Tamko Building Products, Inc.  <b>Address:</b> 220 West 4th Street, Joplin, MO 64801  <b>Contact:</b> Aaron Phillips  <b>Phone:</b> (417) 624-6644 <b>Fax:</b> (800) 841-1925  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Elements Dockboard" composite deck board, 1.4" thick x 5.25" width, all colors.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2044:0004	<p><b>Company:</b> Tamko Building Products, Inc.  <b>Address:</b> 220 West 4th Street, Joplin, MO 64801  <b>Contact:</b> Aaron Phillips  <b>Phone:</b> (417) 624-6644 <b>Fax:</b> (800) 841-1925  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model Envision composite decking board  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>FIBER COMPOSITES, LLC</b>	
8110-2045:0006	<p><b>Company:</b> FIBER COMPOSITES, LLC  <b>Address:</b> 181 Random Drive, New London, NC 28127  <b>Contact:</b> Rick Lappin  <b>Phone:</b> (704) 463-7120  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Veranda® ArmorGuard™ (ArmorGuard/Protect) composite deck board with 3-sided capstock, 0.92" thick x 5 1/8' width.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2045:0007	<p><b>Company:</b> FIBER COMPOSITES, LLC  <b>Address:</b> 181 Random Drive, New London, NC 28127  <b>Contact:</b> Rick Lappin  <b>Phone:</b> (704) 463-7120  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Veranda® ArmorGuard™ (ArmorGuard/ProTect) composite deck plank material 15/16" thick x 5-5/16" wide with a scalloped bottom measuring 3/4" at the minimum distance.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2045:0008	<p><b>Company:</b> FIBER COMPOSITES, LLC  <b>Address:</b> 181 Random Drive, New London, NC 28127  <b>Contact:</b> Rick Lappin  <b>Phone:</b> (704) 463-7120  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Fiberon Paramount (PVC) composite 15/16" thick X 5 1/2" width rounded or grooved edge planks.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>GOSSEN CORPORATION</b>	
8110-2047:0001	<p><b>Company:</b> GOSSEN CORPORATION  <b>Address:</b> 2030 W. Bender Road, Milwaukee, WI 53209  <b>Contact:</b> Bob Simon  <b>Phone:</b> (414) 228-9800 <b>Fax:</b> (414) 228-9077  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Passport" Cellular PVC deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>INTEPLAST WORLD-PAK</b>	
8110-2048:0001	<p><b>Company:</b> INTEPLAST WORLD-PAK  <b>Address:</b> 9 Peach Hill Road, Livingston, NJ 07039  <b>Contact:</b> Raphael Li  <b>Phone:</b> (626) 536-0683 <b>Fax:</b> (973) 994-8007  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "TUF DECK™" extruded PVC composite square edge deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>TimberTech Ltd.</b>	
8110-2051:0001	<p><b>Company:</b> TimberTech Ltd.  <b>Address:</b> 894 Prairie Avenue, Wilmington, OH 45177  <b>Contact:</b> Charles Herr  <b>Phone:</b> (937) 655-5297 <b>Fax:</b> (937) 655-5241  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "DockSider™ Plank" wood plastic composite (WPC) deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2051:0003	<p><b>Company:</b> TimberTech Ltd.  <b>Address:</b> 894 Prairie Avenue, Wilmington, OH 45177  <b>Contact:</b> Charles Herr  <b>Phone:</b> (937) 655-5297 <b>Fax:</b> (937) 655-5241  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "ReliaBoard™" HDPE composite deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2051:0004	<p><b>Company:</b> TimberTech Ltd.  <b>Address:</b> 894 Prairie Avenue, Wilmington, OH 45177  <b>Contact:</b> Charles Herr  <b>Phone:</b> (937) 655-5297 <b>Fax:</b> (937) 655-5241  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "TwinFinish™ Plank" wood plastic composite (WPC) deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2051:0005	<p><b>Company:</b> TimberTech Ltd.  <b>Address:</b> 894 Prairie Avenue, Wilmington, OH 45177  <b>Contact:</b> Charles Herr  <b>Phone:</b> (937) 655-5297 <b>Fax:</b> (937) 655-5241  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "TimberTech XLM™" plastic composite deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>TREX COMPANY, INC.</b>	
8110-2052:0002	<p><b>Company:</b> TREX COMPANY, INC.  <b>Address:</b> 245 Capitol Lane, Winchester, VA 22602  <b>Contact:</b> Kyle Lancaster  <b>Phone:</b> (540) 542-6854 <b>Fax:</b> (540) 678-3002  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Trex Escapes" cellular PVC composite deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2052:0004	<p><b>Company:</b> TREX COMPANY, INC.  <b>Address:</b> 245 Capitol Lane, Winchester, VA 22602  <b>Contact:</b> Kyle Lancaster  <b>Phone:</b> (540) 542-6854 <b>Fax:</b> (540) 678-3002  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Trex® Transcend®" composite deck board, square edge, nominal 1" thick x 5-1/2" width, density of 4.85lbs/linear ft.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

# 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>SABRA INTERNATIONAL, INC.</b>	
8110-2053:0100	<p><b>Company:</b> SABRA INTERNATIONAL, INC.  <b>Address:</b> 300 71st Street, Suite 430, Miami Beach, FL 33141  <b>Contact:</b> Jim VanPelt  <b>Phone:</b> (863) 229-8456 <b>Fax:</b> (863) 229-8359  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Sabra Brand "IPE" solid wood square edge deck board.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>BLUELINX</b>	
8110-2054:0001	<p><b>Company:</b> BLUELINX  <b>Address:</b> 901 Bay Marina Drive, National City, CA 91950  <b>Contact:</b> Dave Gorham  <b>Phone:</b> (951) 212-8063 <b>Fax:</b> (851) 246-2122  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Bluelinx Mangaris Diamond", Merbau hardwood deck board, 3/4" thick x 5-1/2" wide, 1.63 lb/lineal foot (57 lb/cu.ft), reddish brown color.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8110-2054:0102	<p><b>Company:</b> BLUELINX  <b>Address:</b> 901 Bay Marina Drive, National City, CA 91950  <b>Contact:</b> Dave Gorham  <b>Phone:</b> (951) 212-8063 <b>Fax:</b> (851) 246-2122  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Mangaris Red (Red Balau Hardwood Decking) 5-1/2" X 3/4".  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Redwood Empire</b>	
8110-2065:0001	<p><b>Company:</b> Redwood Empire  <b>Address:</b> PO Box 1300, Morgan Hill, CA 95038  <b>Contact:</b> Kevin Henley  <b>Phone:</b> (408) 779-7354 <b>Fax:</b> (408) 778-1076  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Redwood Empire Brand "IPE" Hardwood decking materials. Dimensions 1" x 6" or 5/4" x 6" x 2".  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>KAYU INTERNATIONAL INC.</b>	
8110-2069:0001	<p><b>Company:</b> KAYU INTERNATIONAL INC.  <b>Address:</b> 11117 SW Greenburg Rd., Tigard, OR 97223  <b>Contact:</b> Natalie Smith  <b>Phone:</b> (503) 557-7296 <b>Fax:</b> (503) 557-7262  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> KAYU® Batu (Red Balau) solid hardwood board, reddish brown color, covers products products *nominal 1" and thicker x nominal 4" and wider , nominal density of 55.8 lbs/cubic feet.  <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>Tiger Deck, LLC</b>	
<u>8110-2077:0100</u>	<b>Company:</b> Tiger Deck, LLC <b>Address:</b> P.O. Box 830, Wilsonville, OR 97070 <b>Contact:</b> Bob Hafner <b>Phone:</b> (503) 625-1747 <b>Fax:</b> (503) 625-7342 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> "Tiger Deck" hardwood deck board, grooved edge
<b>CALIFORNIA REDWOOD COMPANY</b>	
<u>8110-2085:0002</u>	<b>Company:</b> CALIFORNIA REDWOOD COMPANY <b>Address:</b> P.O. BOX, Arcata, CA 95518 <b>Contact:</b> Kelly Lusa <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" , Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>MENDOCINO FOREST PRODUCTS</b>	
<u>8110-2086:0002</u>	<b>Company:</b> MENDOCINO FOREST PRODUCTS <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492 <b>Contact:</b> John Russell <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" ,made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>HUMBOLDT REDWOOD COMPANY</b>	
<u>8110-2089:0101</u>	<b>Company:</b> HUMBOLDT REDWOOD COMPANY <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492 <b>Contact:</b> John Russell <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists. <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>SIERRA PACIFIC INDUSTRIES</b>	
<u>8110-2091:0101</u>	<b>Company:</b> SIERRA PACIFIC INDUSTRIES <b>Address:</b> P O Box 496028, Redding, CA 96049 <b>Contact:</b> Mark Pawlicki <b>Phone:</b> (530) 378-8000 <b>Fax:</b> (530) 378-8499 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists. <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>LAUSMANN LUMBER &amp; MOULDING CO</b>	
<u>8110-2092:0101</u>	<b>Company:</b> LAUSMANN LUMBER & MOULDING CO <b>Address:</b> P O BOX 65, LOOMIS, CA 95650 <b>Contact:</b> Joe Lausmann <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists. <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>Unity Forest Products, Inc.</b>	
<u>8110-2094:0103</u>	<b>Company:</b> Unity Forest Products, Inc. <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992 <b>Contact:</b> Enita Elphick <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists. <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>Kubich Lumber</b>	
<u>8110-2104:0001</u>	<b>Company:</b> Kubich Lumber <b>Address:</b> 11099 Mountaineer Trail, Grass Valley, CA 95945 <b>Contact:</b> Tom Rowe <b>Phone:</b> (530) 272-8540 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists. <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>Timber Holdings USA</b>	
<u>8110-2117:0100</u>	<b>Company:</b> Timber Holdings USA <b>Address:</b> 451 S. River Road, Bedford, NH 03110 <b>Contact:</b> Brian Lotz <b>Phone:</b> (414) 750-2336 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Iron Woods™ brand Ipe hardwood deck board <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>Master Mark Plastics</b>	
<u>8110-2133:0100</u>	<b>Company:</b> Master Mark Plastics <b>Address:</b> 30 East Railroad Ave., Albany, MN 56307 <b>Contact:</b> Nick Demuth <b>Phone:</b> (320) 243-7318 <b>Fax:</b> (320) 243-7320 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Rhino Deck - Armadillo <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

## 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>Thermory USA LLC</b>	
8110-2135:0100	<b>Company:</b> Thermory USA LLC <b>Address:</b> 1213 Wilmette Avenue, Suite 208, Wilmette, IL 60091 <b>Contact:</b> Mark Challinor <b>Phone:</b> (847) 256-8828 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Thermally-Modified Ash Deck Boards <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>International Market Strategies/Blue Star Products, USA</b>	
8110-2160:0100	<b>Company:</b> International Market Strategies/Blue Star Products, USA <b>Address:</b> 3105 SE Carlton, Portland, OR 97202 <b>Contact:</b> Mike Moscoe <b>Phone:</b> (503) 777-7008 <b>Fax:</b> (503) 777-5524 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Blue Star® Dark Red Meranti Hardwood Lumber <b>Category:</b> DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.:** 8110-2040:0001 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ADVANCED ENVIRONMENTAL RECYCLING TECHNOLOGIES, INC. 914 North Jefferson,  
Springdale, AR 72764  
Contact: John Dempsey (479) 203-5062 Fax (479) 756-7410  
Email: jdempsey@aert.cc

**DESIGN:** "ChoiceDek® FR" composite wood plastic deck board, 1-3/16" x 5-3/8" , 1-3/8" x 5-3/8" and  
1" x 5.4", all colors. Refer to the manufacturer's installation instructions and product data  
sheets.

**RATING:** Class C Flame Spread (2010 CBC Section 709A.3 will apply)\*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances  
and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and UL label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

Updated 02-23-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2040:0002 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ADVANCED ENVIRONMENTAL RECYCLING TECHNOLOGIES, INC. 914 North Jefferson,  
Springdale, AR 72764  
Contact: John Dempsey (479) 203-5062 Fax (479) 756-7410  
Email: jdempsey@aert.cc

**DESIGN:** "MoistureShield® FR" composite wood plastic deck board, 1-3/16" x 5-3/8" , 1-3/8" x 5-3/8"  
and 1" x 5.4", all colors. Refer to the manufacturer's installation instructions and product  
data sheets.

**RATING:** Class C Flame Spread (2010 CBC Section 709A.3 will apply)\*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances  
and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and UL label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

Update 02-22-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

LISTING No. 8110-2044:0001 Page 1 of 1

CATEGORY: 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: Tamko Building Products, Inc. 220 West 4th Street, Joplin, MO 64801  
Contact: Aaron Phillips (417) 624-6644 Fax (800) 841-1925  
Email: aaron\_phillips@tamko.com

DESIGN: "EverGrain" composite deck board, 15/16" thick x 5.5" width. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Class C Flame Spread (2010 CBC Section 709A.3 will apply)\*

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and UL label.

APPROVAL: Listed as decking materials for use in the Wildland Urban Interface areas.

NOTE: Test Protocol SFM 12-7A-4A

\*Updated 02-22-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014** Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2044:0002 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Tamko Building Products, Inc. 220 West 4th Street, Joplin, MO 64801  
Contact: Aaron Phillips (417) 624-6644 Fax (800) 841-1925  
Email: aaron\_phillips@tamko.com

**DESIGN:** "EverGrain" composite deck board, 1-7/16" thick x 5.5" width. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class C Flame Spread (2010 CBC Section 709A.3 will apply)\*

**INSTALLATION:** In accordance with listee's printed installation instructions, NFPA 72, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and UL label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

Updated 02-23-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2044:0003 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Tamko Building Products, Inc. 220 West 4th Street, Joplin, MO 64801  
Contact: Aaron Phillips (417) 624-6644 Fax (800) 841-1925  
Email: aaron\_phillips@tamko.com

**DESIGN:** "Elements Dockboard" composite deck board, 1.4" thick x 5.25" width, all colors. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class C Flame Spread (2010 CBC Section 709A.3 will apply)\*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and UL label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

Updated 02-23-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2044:0004 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Tamko Building Products, Inc. 220 West 4th Street, Joplin, MO 64801  
Contact: Aaron Phillips (417) 624-6644 Fax (800) 841-1925  
Email: aaron\_phillips@tamko.com

**DESIGN:** Model Envision composite decking board. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class C Flame Spread (2010 CBC Section 709A.3 will apply)

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name and UL label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

07-23-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2045:0006 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** FIBER COMPOSITES, LLC181 Random Drive, New London, NC 28127  
Contact: Rick Lappin (704) 463-7120  
Email: rickl@fiberondecking.com

**DESIGN:** Veranda® ArmorGuard™ (ArmorGuard/Protect) composite deck board with 3-sided capstock, 0.92" thick x 5 1/8' width. Square Edge compositions at an edge-to-edge gap spacing of a maximum of 1/8", Scalloped bottom, Nominal 1" thick at edge, 5.3" wide. Refer to manufacturer's installation instructions.

**RATING:** SFM 12-7A-4A

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A.

02-02-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2045:0007 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** FIBER COMPOSITES, LLC 181 Random Drive, New London, NC 28127  
Contact: Rick Lappin (704) 463-7120  
Email: rickl@fiberondecking.com

**DESIGN:** Veranda® ArmorGuard™ (ArmorGuard/ProTect) composite deck plank material 15/16" thick x 5-5/16" wide with a scalloped bottom measuring 3/4" at the minimum distance. Edge to edge gap spacing maximum 1/8". Refer to manufacturer's installation instructions.

**RATING:** SFM 12-7A-4A

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A.

01-23-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2045:0008

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** FIBER COMPOSITES, LLC 181 Random Drive, New London, NC 28127  
Contact: Rick Lappin (704) 463-7120  
Email: rickl@fiberondecking.com

**DESIGN:** Fiberon Paramount (PVC) composite 15/16" thick X 5 1/2" width rounded or grooved edge planks. 3/16" edge to edge spacing. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** SFM 12-7A-4A

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

04-10-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2047:0001 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** GOSSEN CORPORATION 2030 W. Bender Road, Milwaukee, WI 53209  
Contact: Bob Simon (414) 228-9800 Fax (414) 228-9077  
Email: rsimon@gossencorp.com

**DESIGN:** "Passport" Cellular PVC deck board, brown color, 1" thick x 5 1/2" width, rounded edges.

**RATING:** Class B Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**NOTE:** Test Protocol 12-7A-4, Part A only, Accelerated weathering.

8-31-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

**Date Issued:** **July 01, 2014**

*Listing Expires* **June 30, 2015**

**Authorized By:** **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

LISTING No. 8110-2048:0001 Page 1 of 1

CATEGORY: 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: INTEPLAST WORLD-PAK9 Peach Hill Road, Livingston, NJ 07039  
Contact: Raphael Li (626) 536-0683 Fax (973) 994-8007  
Email: rli@inteplast.com

DESIGN: "TUF DECK™" extruded PVC composite square edge deck board, 15/16" thick x 5-7/16" width, 1.65 lb/lineal foot. . Refer to the manufacturer's installation instructions and product data sheets.

RATING: Class A Flame Spread.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and \_\_\_\_\_ label (Pending).

APPROVAL: Listed as decking materials for use in the Wildland Urban Interface areas.

NOTE: Test Protocol 12-7A-4A

issued 06-13-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2051:0001

**CATEGORY:** 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TimberTech Ltd. 894 Prairie Avenue, Wilmington, OH 45177  
Contact: Charles Herr (937) 655-5297 Fax (937) 655-5241  
Email: cherr@timbertech.com

**DESIGN:** "DockSider™ Plank" wood plastic composite (WPC) deck board, square edge, 1-1/4" thick x 5-1/2" wide, 3-1/2 lb/lineal foot. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2051:0003

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TimberTech Ltd. 894 Prairie Avenue, Wilmington, OH 45177  
Contact: Charles Herr (937) 655-5297 Fax (937) 655-5241  
Email: cherr@timbertech.com

**DESIGN:** "ReliaBoard™" HDPE composite deck board, square edge, scalloped back surface, 3/4" at thinnest portion, 15/16" at thickest, 5-3/8" wide and nominally 2.4 lb/lineal foot. . Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2051:0004

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TimberTech Ltd. 894 Prairie Avenue, Wilmington, OH 45177  
Contact: Charles Herr (937) 655-5297 Fax (937) 655-5241  
Email: cherr@timbertech.com

**DESIGN:** "TwinFinish™ Plank" wood plastic composite (WPC) deck board, square edge and grooved, 1" thick x 5-7/16" wide, 2.7 to 2.8 lb/lineal foot. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2051:0005

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TimberTech Ltd.894 Prairie Avenue, Wilmington, OH 45177  
Contact: Charles Herr (937) 655-5297 Fax (937) 655-5241  
Email: cherr@timbertech.com

**DESIGN:** "TimberTech XLM™" plastic composite deck board, square edge and grooved, 1" thick x 5-1/2" wide, nominal 1.6 lb/lineal foot. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4, Part A only, Accelerated weathering.

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2052:0002 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TREX COMPANY, INC. 245 Capitol Lane, Winchester, VA 22602  
Contact: Kyle Lancaster (540) 542-6854 Fax (540) 678-3002  
Email: klancaster@trex.com

**DESIGN:** "Trex Escapes" cellular PVC composite deck board, nominal 1" thick x 5-1/2" width, nominal density of 1.6 lbs/linear ft. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class A Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, NFPA 72, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

Issued 06-13-11bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2052:0004

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** TREX COMPANY, INC. 245 Capitol Lane, Winchester, VA 22602  
Contact: Kyle Lancaster (540) 542-6854 Fax (540) 678-3002  
Email: klancaster@trex.com

**DESIGN:** "Trex® Transcend®" composite deck board, square edge, nominal 1" thick x 5-1/2" width, density of 4.85lbs/linear ft.

**RATING:** Test Protocol 12-7A-4, Part A only, Accelerated weathering.  
Flame Spread Class B

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes & ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee's name, model designation, rating and SFM label.

**APPROVAL:** Listed as decking materials that in compliance with the 2010 California Building code . Chapter 7A.

04-11-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8110-2053:0100 Page 1 of 1

CATEGORY: 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: SABRA INTERNATIONAL, INC. 300 71st Street, Suite 430, Miami Beach, FL 33141  
Contact: Jim VanPelt (863) 229-8456 Fax (863) 229-8359  
Email: jim@LBRtimber.com

DESIGN: Sabra Brand "IPE" solid wood square edge deck board, 3/4" thick x 5-5/16" width, nominal density of 63.2 lb/cu.ft.. Refer to manufacturer's installation instructions and data sheet for details.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number and SFM label

APPROVAL: Listed as solid wood decking material for used in the Wildland Urban Interface areas.

NOTE: Test Protocol 12-7A-4, Part A only,

06-27-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



Page 1 of 1

**LISTING No.** 8110-2054:0001

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** BLUELINX901 Bay Marina Drive, National City, CA 91950  
Contact: Dave Gorham (951) 212-8063 Fax (851) 246-2122  
Email: dave.gorham@bluelinxco.com

**DESIGN:** "Bluelinx Mangaris Diamond", Merbau hardwood deck board, 3/4" thick x 5-1/2" wide, 1.63 lb/lineal foot (57 lb/cu.ft), reddish brown color. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class A Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking material for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2054:0102 Page 1 of 1

**CATEGORY:** 8110 – DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** BLUELINX901 Bay Marina Drive, National City, CA 91950  
Contact: Dave Gorham (951) 212-8063 Fax (851) 246-2122  
Email: dave.gorham@bluelinxco.com

**DESIGN:** \*Mangaris Red (Red Balau Hardwood Decking) 5-1/2" X 3/4" (square edge). Maximum 3/16" edge to edge spacing. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class A Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as decking material for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

\*Rev 06-12-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8110-2065:0001 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Redwood Empire PO Box 1300, Morgan Hill, CA 95038  
Contact: Kevin Henley (408) 779-7354 Fax (408) 778-1076  
Email: khenley@redwoodemp.com

**DESIGN:** Redwood Empire Brand "IPE" Hardwood decking materials. Dimensions 1" x 6" or 5/4" x 6" x 2". Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spead

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

Issued 06-06-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

**Date Issued:** **July 01, 2014** *Listing Expires* **June 30, 2015**

**Authorized By:** **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2069:0001

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** KAYU INTERNATIONAL INC. 11117 SW Greenburg Rd., Tigard, OR 97223  
Contact: Natalie Smith (503) 557-7296 Fax (503) 557-7262  
Email: Natalie@kayu.com

**DESIGN:** KAYU® Batu (Red Balau) solid hardwood board, reddish brown color, covers products \*nominal 1" and thicker x nominal 4" and wider, nominal density of 55.8 lbs/cubic feet. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class A Flame Spread.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking material for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

Page 1 of 1

\*Rev. 11-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2077:0100 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Tiger Deck, LLC, P.O. Box 830, Wilsonville, OR 97070  
Contact: Bob Hafner (503) 625-1747 Fax (503) 625-7342  
Email: bob@tigerdeck.com

**DESIGN:** "Tiger Deck" hardwood decking materials including grooved and non-grooved deck board. Nominal 1" x 4", 5/4" x 4", 1" x 6", and 5/4" x 6". Deck may employ finish components as described in the product data sheet. Refer to the manufacturer's installation instructions.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-4A

09-12-11 mt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2085:0002

Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com

**DESIGN:** Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

**XLF:** 8110-2041:0002

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

**Date Issued:** July 01, 2014

*Listing Expires* June 30, 2015

**Authorized By:** JAMES PARSEGIAN, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2086:0002 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

**XLF:** 8110-2041:0002

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8110-2089:0101 Page 1 of 1

CATEGORY: 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: HUMBOLDT REDWOOD COMPANY/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

DESIGN: Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

RATING: Class B Flame Spread

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

NOTE: Test Protocol SFM 12-7A-4A

XLF: 8110-2041:0002

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

Page 1 of 1

**LISTING No.** 8110-2091:0101

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SIERRA PACIFIC INDUSTRIES P O Box 496028, Redding, CA 96049  
Contact: Mark Pawlicki (530) 378-8000 Fax (530) 378-8499  
Email: mpawlicki@spi-ind.com

**DESIGN:** Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

**XLf:** 8110-2041:0002

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2092:0101

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 652-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

**XLF:** 8110-2041:0002

Page 1 of 1

12-20-11 MFV



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2094:0103  
**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)  
**LISTEE:** Unity Forest Products, Inc. P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

Page 1 of 1

**DESIGN:** Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

**XLF:** 8110-2041:0002

I-10-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8110-2104:0001 Page 1 of 1

CATEGORY: 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: Kubich Lumber 11099 Mountaineer Trail, Grass Valley, CA 95945  
Contact: Tom Rowe (530) 272-8540  
Email: tmrowe@sbbmail.com

DESIGN: Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

RATING: Class B Flame Spread

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

NOTE: Test Protocol SFM 12-7A-4A

XLF: 8110-2041:0002

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2117:0100 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Timber Holdings USA451 S. River Road, Bedford, NH 03110  
Contact: Brian Lotz (414) 750-2336  
Email: brian@ironwoods.com

**DESIGN:** Iron Woods™ brand lpe hardwood deck board 5 1/2"\*(minimum) X 3/4"\*(minimum). Maximum 3/16" edge-to-edge plank spacing. Refer to the manufacturer's installation instructions and product data sheets.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

\*Rev 05-09-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2133:0100 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Master Mark Plastics 30 East Railroad Ave., Albany, MN 56307  
Contact: Nick Demuth (320) 243-7318 Fax (320) 243-7320  
Email: nick.demuth@mastermark.com

**DESIGN:** Rhino Deck - Armadillo with dimensions of 5.24" x .915" and corner radius of 0.2. Weight of 2.25 lbs/ft.  
Refer to the manufacturer's installation instructions and product data sheets.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and \*Intertek label.

**APPROVAL:** Listed as decking materials for use in the Wildland Urban Interface areas. Refer to manufacturer's Installation Manual for details.

**NOTE:** SFM Test Protocol 12-7A-4A.

\*Rev 10-02-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8110-2135:0100 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Thermory USA LLC 1213 Wilmette Avenue, Suite 208, Wilmette, IL 60091  
Contact: Mark Challinor (847) 256-8828  
Email: mark@thermoryusa.com

**DESIGN:** Thermally-Modified Ash Deck Boards with dimensions of 3/4" x 5-7/8" or 1.02" x 5.7" with a maximum of 3/16" edge-to-edge spacing.  
Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class B Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as wood decking materials for use in the Wildland Urban Interface areas. Refer to manufacturer's Installation Manual for details.

**NOTE:** Test Protocol SFM-12-7A-4A

09-25-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8110-2160:0100 Page 1 of 1

**CATEGORY:** 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** International Market Strategies/Blue Star Products, USA3105 SE Carlton, Portland, OR  
97202  
Contact: Mike Moscoe (503) 777-7008 Fax (503) 777-5524  
Email: bluestardecks@aol.com

**DESIGN:** Blue Star® Dark Red Meranti Hardwood Lumber 3/4" X 5-1/2" with 3/16" edge to edge spacing. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Class A Flame Spread

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as decking material for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-4A

06-04-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

## 8120 – EXTERIOR WINDOWS FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>Riviera Bronze Manufacturing</b>	
<u>8120-2120:0100</u>	<b>Company:</b> Riviera Bronze Manufacturing <b>Address:</b> 1895 North Ventura Avenue, Ventura, CA 93001 <b>Contact:</b> Sid Anderson <b>Phone:</b> (805) 653-1943 <b>Fax:</b> (805) 653-1942 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Metal-glazed window with structural silicone glazing and 1/4" (minimum) laminated annealed glass or insulated glass units with a minimum of one tempered pane. <b>Category:</b> EXTERIOR WINDOWS FOR WILDLAND URBAN INTERFACE (W.U.I)

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8120-2120.0100 Page 1 of 1

**CATEGORY:** 8120 -- EXTERIOR WINDOWS FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Riviera Bronze Manufacturing 1895 North Ventura Avenue, Ventura, CA 93001  
Contact: Sid Anderson (805) 653-1943 Fax (805) 653-1942  
Email: sea@rivierabronze.com

**DESIGN:** Metal-glazed window with structural silicone glazing and 1/4" (minimum) laminated annealed glass \*or insulated glass units with a minimum of one tempered pane. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Window for use in the Wildland Urban Interface areas.

\*Rev 04-03-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>APA-THE ENGINEERED WOOD ASSOCIATION</b>	
8140-2020:0001	<p><b>Company:</b> APA-THE ENGINEERED WOOD ASSOCIATION  <b>Address:</b> 7011 South 19th Street, Tacoma, WA 98466  <b>Contact:</b> Borjen Yeh  <b>Phone:</b> (253) 620-7467 <b>Fax:</b> (253) 565-7265  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "APA 303@" plywood siding with shiplap edges.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2020:0002	<p><b>Company:</b> APA-THE ENGINEERED WOOD ASSOCIATION  <b>Address:</b> 7011 South 19th Street, Tacoma, WA 98466  <b>Contact:</b> Borjen Yeh  <b>Phone:</b> (253) 620-7467 <b>Fax:</b> (253) 565-7265  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "APA 303@" plywood siding with reverse-board and batten.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>CEDAR VALLEY MANUFACTURING</b>	
8140-2023:0001	<p><b>Company:</b> CEDAR VALLEY MANUFACTURING  <b>Address:</b> 943 San Felipe Road, Hollister, CA 95023  <b>Contact:</b> Jon Whorley  <b>Phone:</b> (831) 636-8110 <b>Fax:</b> (831) 636-8109  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Cedar Valley FTX Pressure Treated 1-Course Cedar Shingle Panel.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2023:0002	<p><b>Company:</b> CEDAR VALLEY MANUFACTURING  <b>Address:</b> 943 San Felipe Road, Hollister, CA 95023  <b>Contact:</b> Jon Whorley  <b>Phone:</b> (831) 636-8110 <b>Fax:</b> (831) 636-8109  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Cedar Valley "California Stack" 1-Course Cedar Shingle Siding Panel.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2023:0100	<p><b>Company:</b> CEDAR VALLEY MANUFACTURING  <b>Address:</b> 943 San Felipe Road, Hollister, CA 95023  <b>Contact:</b> Jon Whorley  <b>Phone:</b> (831) 636-8110 <b>Fax:</b> (831) 636-8109  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Cedar Valley Cedar-Lam 1 x 4 tongue &amp; groove siding/paneling that has a 1/8" western red cedar veneer bonded to a 1/2" CDX plywood backer.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>COLLINS PRODUCTS, LLC</b>	
8140-2025:0006	<p><b>Company:</b> COLLINS PRODUCTS, LLC  <b>Address:</b> 6410 Highway 66, Klamath Falls, OR 97601  <b>Contact:</b> Jeff Cronin  <b>Phone:</b> (541) 885-3303 <b>Fax:</b> (541) 885-3285  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> TruWood®7/16" Panel Siding, TruWood®1/2" Panel Siding, TruWood®7/16" Lap Siding, and TruWood®1/2" Lap Siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>JAMES HARDIE BUILDING PRODUCTS, INC.</b>	
8140-2026:0001	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Artisan®" lap siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2026:0002	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Cemplank®" lap siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2026:0003	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Cempanel®" vertical siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2026:0004	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "HardieShingle™" panel.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2026:0005	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "HardiePlank™" lap siding.</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>LOUISIANA-PACIFIC</b>	
8140-2027:0001	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP SmartSide® Precision Series" exterior lap siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2027:0002	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP SmartSide® Precision Series" exterior panel siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2027:0003	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP SmartSide® Foundation Series" exterior lap siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2027:0004	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP SmartSide® Foundation Series" exterior panel siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2027:0005	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP FlameBlock™" sheathing.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2027:0006	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP FlameBlock™" sheathing.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>NICHIHA USA, INC.</b>	
<u>8140-2029:0001</u>	<p><b>Company:</b> NICHIHA USA, INC.  <b>Address:</b> 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  <b>Contact:</b> Ryuji Hotta  <b>Phone:</b> (770) 805-9466 <b>Fax:</b> (770) 805-9467  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> EX Series "Field Stone" Brick and Stone panels siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8140-2029:0002</u>	<p><b>Company:</b> NICHIHA USA, INC.  <b>Address:</b> 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  <b>Contact:</b> Ryuji Hotta  <b>Phone:</b> (770) 805-9466 <b>Fax:</b> (770) 805-9467  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NichiFrontier, NichiStaggered and NishiStraight Shake panels siding  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8140-2029:0003</u>	<p><b>Company:</b> NICHIHA USA, INC.  <b>Address:</b> 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  <b>Contact:</b> Ryuji Hotta  <b>Phone:</b> (770) 805-9466 <b>Fax:</b> (770) 805-9467  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NichiBoard smooth and cedar textures, unprimed cementitious board.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8140-2029:0004</u>	<p><b>Company:</b> NICHIHA USA, INC.  <b>Address:</b> 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  <b>Contact:</b> Ryuji Hotta  <b>Phone:</b> (770) 805-9466 <b>Fax:</b> (770) 805-9467  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NichiPanel smooth and cedar textures, unprimed cementitious panel.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>ROSEBURG FOREST PRODUCTS CO.</b>	
<u>8140-2031:0001</u>	<p><b>Company:</b> ROSEBURG FOREST PRODUCTS CO.  <b>Address:</b> PO Box 1088, Roseburg, OR 97470  <b>Contact:</b> Dennis Cunningham  <b>Phone:</b> (541) 464-7057 <b>Fax:</b> (541) 874-3342  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Breckenridge" Siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2031:0002	<p><b>Company:</b> ROSEBURG FOREST PRODUCTS CO.  <b>Address:</b> PO Box 1088, Roseburg, OR 97470  <b>Contact:</b> Dennis Cunningham  <b>Phone:</b> (541) 464-7057 <b>Fax:</b> (541) 874-3342  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Douglas Fir" siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2031:0003	<p><b>Company:</b> ROSEBURG FOREST PRODUCTS CO.  <b>Address:</b> PO Box 1088, Roseburg, OR 97470  <b>Contact:</b> Dennis Cunningham  <b>Phone:</b> (541) 464-7057 <b>Fax:</b> (541) 874-3342  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "DuraTemp™" siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2031:0004	<p><b>Company:</b> ROSEBURG FOREST PRODUCTS CO.  <b>Address:</b> PO Box 1088, Roseburg, OR 97470  <b>Contact:</b> Dennis Cunningham  <b>Phone:</b> (541) 464-7057 <b>Fax:</b> (541) 874-3342  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "DuraTemp™" siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>SHAKERTOWN</b>	
8140-2032:0001	<p><b>Company:</b> SHAKERTOWN  <b>Address:</b> 1200 Kerron Street, Winlock, WA 98596  <b>Contact:</b> Mark Rutledge  <b>Phone:</b> (360) 785-3501 <b>Fax:</b> (360) 785-3076  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "Shakertown® Craftman™" 1-course Cedar Shingle Panel siding.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2032:0002	<p><b>Company:</b> SHAKERTOWN  <b>Address:</b> 1200 Kerron Street, Winlock, WA 98596  <b>Contact:</b> Mark Rutledge  <b>Phone:</b> (360) 785-3501 <b>Fax:</b> (360) 785-3076  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Shakertown® Craftsman™ 1-Course Cedar Shingle Panel.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>Nusku Partners LLC</b>	
8140-2064:0002	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G V Joint &amp; CV" siding CRA #17 Pattern Number 616 and 617, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0003	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G Butt Joint S2S" siding CRA #17 Pattern Number 633 and 634, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0004	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G Butt Joint S2S" siding CRA #17 Pattern Number 633EE and 634EE, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0005	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G V Joint S2S V 1 Side" siding CRA #17 Pattern Number 708, 715 and 716, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2064:0006	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 708R, 715R and 716R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0007	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G V Joint S2S V 1 Side" siding CRA #17 Pattern Number 711, 712 and 713, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0008	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "T&amp;G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 726R, 727R and 728R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0012	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "Shiplap Butt JT" siding CRA #17 Pattern Number 761, 762 and 763, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2064:0013	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "1" Channel Shiplap" siding CRA #17 Pattern Number 774, 775 and 776, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0015	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "RAB R/Sawn Face" siding CRA #17 Pattern Number 391, 392, 393 and 394 Clear Fire Retardant Fingerjoint Redwood, minimum 3/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0016	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "RAB R/Sawn Face" siding CRA #17 Pattern Number 476, 477, 478 and 479 Clear Fire Retardant Fingerjoint Redwood, minimum 1 1/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0018	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "2 Lap" siding CRA #17 Pattern Number 433, Clear Fire Retardant Fingerjoint Redwood, minimum 1x10 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only Refer to the manufacturer's installation instructions and product data sheets.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2064:0019	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> *Nusku Fireblocker "2 Lap" siding CRA #17 Pattern Number 431, Clear Fire Retardant Fingerjoint Redwood, minimum 1x8 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0020	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "T&amp;G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 711R, 712R and 713R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0021	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "Channel Shiplap" siding CRA #17 Pattern Number 773, Clear Fire Retardant Fingerjoint Redwood, minimum 1x10 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0022	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "Cove Shiplap" siding CRA #17 Pattern Number 770, 771 and 772, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2064:0023	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "V Joint Shiplap" siding CRA #17 Pattern Number 793, 794 and 795, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0024	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "RAB Smooth Face" siding CRA #17 Pattern Number 371, 372, and 373, Clear Fire Retardant Fingerjoint Redwood, minimum 3/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2064:0025	<p><b>Company:</b> Nusku Partners LLC  <b>Address:</b> 4501 Brickell Privado Street, Ontario, CA 91761  <b>Contact:</b> Tim Hummel  <b>Phone:</b> (909) 974-0180 <b>Fax:</b> (909) 974-0181  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> NuSku Fireblocker "2 Lap" siding CRA #17 Pattern Number 430, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>PLY GEM SIDING GROUP</b>	
8140-2070:0001	<p><b>Company:</b> PLY GEM SIDING GROUP  <b>Address:</b> 2405 Campbell Road, Sidney, OH 45364  <b>Contact:</b> Alan Hoying  <b>Phone:</b> (937) 498-6720 <b>Fax:</b> (937) 498-6127  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model "Cedar Discovery" polypropylene siding panels. Panels are 64" x 14" with nominal thickness of 0.1".  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2070:0002	<p><b>Company:</b> PLY GEM SIDING GROUP  <b>Address:</b> 2405 Campbell Road, Sidney, OH 45364  <b>Contact:</b> Alan Hoying  <b>Phone:</b> (937) 498-6720 <b>Fax:</b> (937) 498-6127  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model "Mastic Brentwood" PVC siding panels. Panels are 12' x 10" with nominal thickness of 0.04".  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2070:0003	<p><b>Company:</b> PLY GEM SIDING GROUP  <b>Address:</b> 2405 Campbell Road, Sidney, OH 45364  <b>Contact:</b> Alan Hoying  <b>Phone:</b> (937) 498-6720 <b>Fax:</b> (937) 498-6127  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model "Mastic Barkwood" PVC siding panels. Panels are 12' x 10" with nominal thickness of 0.048".  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2070:0004	<p><b>Company:</b> PLY GEM SIDING GROUP  <b>Address:</b> 2405 Campbell Road, Sidney, OH 45364  <b>Contact:</b> Alan Hoying  <b>Phone:</b> (937) 498-6720 <b>Fax:</b> (937) 498-6127  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model Mastic Quest Vinyl Siding (Non-Weathered)  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2070:0005	<p><b>Company:</b> PLY GEM SIDING GROUP  <b>Address:</b> 2405 Campbell Road, Sidney, OH 45364  <b>Contact:</b> Alan Hoying  <b>Phone:</b> (937) 498-6720 <b>Fax:</b> (937) 498-6127  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model Mastic Structure Vinyl Siding (Non-Weathered).  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>CALIFORNIA REDWOOD COMPANY</b>	
8140-2085:0001	<p><b>Company:</b> CALIFORNIA REDWOOD COMPANY  <b>Address:</b> P.O. BOX, Arcata, CA 95518  <b>Contact:</b> Kelly Lusa  <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin and Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2085:0003	<p><b>Company:</b> CALIFORNIA REDWOOD COMPANY  <b>Address:</b> P.O. BOX, Arcata, CA 95518  <b>Contact:</b> Kelly Lusa  <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Tongued &amp; Grooved, Shiplap, V Shiplap (Edge Vee One Side) and Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side)  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2085:0004	<p><b>Company:</b> CALIFORNIA REDWOOD COMPANY  <b>Address:</b> P.O. BOX, Arcata, CA 95518  <b>Contact:</b> Kelly Lusa  <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Rabbeted Bevel, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2085:0005	<p><b>Company:</b> CALIFORNIA REDWOOD COMPANY  <b>Address:</b> P.O. BOX, Arcata, CA 95518  <b>Contact:</b> Kelly Lusa  <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Board and Batten, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2085:0006	<p><b>Company:</b> CALIFORNIA REDWOOD COMPANY  <b>Address:</b> P.O. BOX, Arcata, CA 95518  <b>Contact:</b> Kelly Lusa  <b>Phone:</b> (707) 268-3096 <b>Fax:</b> (707) 268-3089  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Board on Board, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>MENDOCINO FOREST PRODUCTS</b>	
8140-2086:0001	<p><b>Company:</b> MENDOCINO FOREST PRODUCTS  <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin and Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap.</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2086:0003	<p><b>Company:</b> MENDOCINO FOREST PRODUCTS  <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding ,Tongued &amp; Grooved, Shiplap, V Shiplap (Edge Vee One Side) and Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side)  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2086:0004	<p><b>Company:</b> MENDOCINO FOREST PRODUCTS  <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Rabbeted Bevel, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2086:0005	<p><b>Company:</b> MENDOCINO FOREST PRODUCTS  <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Board and Battens, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2086:0006	<p><b>Company:</b> MENDOCINO FOREST PRODUCTS  <b>Address:</b> 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding, Board on Board, made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>HUMBOLDT REDWOOD COMPANY</b>	
8140-2089:0100	<p><b>Company:</b> HUMBOLDT REDWOOD COMPANY  <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2089:0102	<p><b>Company:</b> HUMBOLDT REDWOOD COMPANY  <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. a. Tongued &amp; Grooved, Shiplap, V Shiplap (Edge Vee One Side). b. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side).  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2089:0103	<p><b>Company:</b> HUMBOLDT REDWOOD COMPANY  <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2089:0104	<p><b>Company:</b> HUMBOLDT REDWOOD COMPANY  <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose. Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2089:0105	<p><b>Company:</b> HUMBOLDT REDWOOD COMPANY  <b>Address:</b> C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  <b>Contact:</b> John Russell  <b>Phone:</b> (707) 620-2977 <b>Fax:</b> (707) 620-2964  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>SIERRA PACIFIC INDUSTRIES</b>	
8140-2091:0100	<p><b>Company:</b> SIERRA PACIFIC INDUSTRIES  <b>Address:</b> P O Box 496028, Redding, CA 96049  <b>Contact:</b> Mark Pawlicki  <b>Phone:</b> (530) 378-8000 <b>Fax:</b> (530) 378-8499  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. a. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin. b. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2091:0102	<p><b>Company:</b> SIERRA PACIFIC INDUSTRIES  <b>Address:</b> P O Box 496028, Redding, CA 96049  <b>Contact:</b> Mark Pawlicki  <b>Phone:</b> (530) 378-8000 <b>Fax:</b> (530) 378-8499  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2091:0103	<p><b>Company:</b> SIERRA PACIFIC INDUSTRIES  <b>Address:</b> P O Box 496028, Redding, CA 96049  <b>Contact:</b> Mark Pawlicki  <b>Phone:</b> (530) 378-8000 <b>Fax:</b> (530) 378-8499  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2091:0104	<p><b>Company:</b> SIERRA PACIFIC INDUSTRIES  <b>Address:</b> P O Box 496028, Redding, CA 96049  <b>Contact:</b> Mark Pawlicki  <b>Phone:</b> (530) 378-8000 <b>Fax:</b> (530) 378-8499  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose. Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>LAUSMANN LUMBER &amp; MOULDING CO</b>	
8140-2092:0100	<p><b>Company:</b> LAUSMANN LUMBER &amp; MOULDING CO  <b>Address:</b> P O BOX 65, LOOMIS, CA 95650  <b>Contact:</b> Joe Lausmann  <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2092:0102	<p><b>Company:</b> LAUSMANN LUMBER &amp; MOULDING CO  <b>Address:</b> P O BOX 65, LOOMIS, CA 95650  <b>Contact:</b> Joe Lausmann  <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. a. Tongued &amp; Grooved, Shiplap, V Shiplap (Edge Vee One Side). b. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side).  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2092:0103	<p><b>Company:</b> LAUSMANN LUMBER &amp; MOULDING CO  <b>Address:</b> P O BOX 65, LOOMIS, CA 95650  <b>Contact:</b> Joe Lausmann  <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2092:0104	<p><b>Company:</b> LAUSMANN LUMBER &amp; MOULDING CO  <b>Address:</b> P O BOX 65, LOOMIS, CA 95650  <b>Contact:</b> Joe Lausmann  <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose. Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2092:0105	<p><b>Company:</b> LAUSMANN LUMBER &amp; MOULDING CO  <b>Address:</b> P O BOX 65, LOOMIS, CA 95650  <b>Contact:</b> Joe Lausmann  <b>Phone:</b> (916) 652-9201 <b>Fax:</b> (916) 652-4464  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Unity Forest Products, Inc.</b>	
8140-2094:0100	<p><b>Company:</b> Unity Forest Products, Inc.  <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992  <b>Contact:</b> Enita Elphick  <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. a. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin. b. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2094:0101	<p><b>Company:</b> Unity Forest Products, Inc.  <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992  <b>Contact:</b> Enita Elphick  <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2094:0102	<p><b>Company:</b> Unity Forest Products, Inc.  <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992  <b>Contact:</b> Enita Elphick  <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. a. Tongued &amp; Grooved, Shiplap, V Shiplap (Edge Vee One Side). b. Tongued &amp; Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side).  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2094:0104	<p><b>Company:</b> Unity Forest Products, Inc.  <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992  <b>Contact:</b> Enita Elphick  <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2094:0105	<p><b>Company:</b> Unity Forest Products, Inc.  <b>Address:</b> P.O. Box 1849, Yuba City, CA 95992  <b>Contact:</b> Enita Elphick  <b>Phone:</b> (530) 671-7152 <b>Fax:</b> (530) 671-7261  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose. Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Kubich Lumber</b>	
8140-2104:0002	<p><b>Company:</b> Kubich Lumber  <b>Address:</b> 11099 Mountaineer Trail, Grass Valley, CA 95945  <b>Contact:</b> Tom Rowe  <b>Phone:</b> (530) 272-8540  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2104:0003	<p><b>Company:</b> Kubich Lumber  <b>Address:</b> 11099 Mountaineer Trail, Grass Valley, CA 95945  <b>Contact:</b> Tom Rowe  <b>Phone:</b> (530) 272-8540  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
8140-2104:0004	<p><b>Company:</b> Kubich Lumber  <b>Address:</b> 11099 Mountaineer Trail, Grass Valley, CA 95945  <b>Contact:</b> Tom Rowe  <b>Phone:</b> (530) 272-8540  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose knots. Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2104:0005	<p><b>Company:</b> Kubich Lumber  <b>Address:</b> 11099 Mountaineer Trail, Grass Valley, CA 95945  <b>Contact:</b> Tom Rowe  <b>Phone:</b> (530) 272-8540  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Solid-sawn "Wood" siding with no through holes or loose. Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Pacific Wood Laminates, Inc.</b>	
8140-2121:0100	<p><b>Company:</b> Pacific Wood Laminates, Inc.  <b>Address:</b> 885 Railroad Ave. PO Box 820, Brookings, OR 97415  <b>Contact:</b> Chris Johnson  <b>Phone:</b> (541) 469-4177 <b>Fax:</b> (541) 469-6153  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "APA 303@" plywood siding with shiplap edges.  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8140-2121:0101	<p><b>Company:</b> Pacific Wood Laminates, Inc.  <b>Address:</b> 885 Railroad Ave. PO Box 820, Brookings, OR 97415  <b>Contact:</b> Chris Johnson  <b>Phone:</b> (541) 469-4177 <b>Fax:</b> (541) 469-6153  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "APA 303@" plywood siding with reverse-board and batten with shiplap edges..  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>



## 8140 – EXTERIOR WALL SIDING FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>Blocks and Cutstock S.A.</b>	
8140-2126:0100	<p><b>Company:</b> Blocks and Cutstock S.A.  <b>Address:</b> 5065 Gold Creek Rd, Auburn, CA 95602 United States  <b>Contact:</b> Richard Smallridge  <b>Phone:</b> (916) 799-8404  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Advantage Plus™ treated Radiata pine siding  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Arauco USA</b>	
8140-2132:0100	<p><b>Company:</b> Arauco USA  <b>Address:</b> 5901 B Peachtree Dunwoody RD NE, Ste 500, Atlanta, GA 30328  <b>Contact:</b> Timothy Pruitt  <b>Phone:</b> (770) 350-1647  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Arauco® TruChoice Treated Radiata pine siding  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>WATKINS SAWMILLS</b>	
8140-2146:0100	<p><b>Company:</b> WATKINS SAWMILLS  <b>Address:</b> P O BOX 457, SUMAS, WA 98295  <b>Contact:</b> Bill Hendricks  <b>Phone:</b> (916) 698-6862 <b>Fax:</b> (916) 372-9562  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Cedar shingles installed over Thermax treated plywood  <b>Category:</b> EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2020:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** APA-THE ENGINEERED WOOD ASSOCIATION 7011 South 19th Street, Tacoma, WA 98466  
Contact: Borjen Yeh (253) 620-7467 Fax (253) 565-7265  
Email: borjen.yeh@apawood.org

**DESIGN:** "APA 303®" plywood siding with shiplap edges, nominal 19/32" thick \*(19/32 Performance Category) or greater and grooves spaced \*no closer than 4" on center or without grooves, and manufactured with veneers of all Southern Pine or Douglas Fir face, back and center with cross piles \*of PS1 Group 1 or 2 species, 4'x8' panel. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas. Refer to listee's Installation Instruction Manual for details.

**NOTE:** Test Protocol SFM 12-7A-1

\*Rev 05-08-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2020:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** APA-THE ENGINEERED WOOD ASSOCIATION 7011 South 19th Street, Tacoma, WA  
98466  
Contact: Borjen Yeh (253) 620-7467 Fax (253) 565-7265  
Email: borjen.yeh@apawood.org

**DESIGN:** "APA 303®" plywood siding with reverse-board and batten with shiplap edges, nominal 19/32" thick (19/32 Performance Category) or greater, grooves spaced no closer than 12" on center or without \*grooves, manufactured with face, back and center of Douglas Fir veneers and cross ply veneers of PS1 Group 1 or 2 species, 4'x8' panel. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas. Refer to listee's Installation Instruction Manual for details.

\*Rev 05-15-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2023:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CEDAR VALLEY MANUFACTURING 943 San Felipe Road, Hollister, CA 95023  
Contact: Jon Whorley (831) 636-8110 Fax (831) 636-8109  
Email: jonw@cedar-valley.com

**DESIGN:** Cedar Valley FTX Pressure Treated 1-Course Cedar Shingle Panel, 7-1/8" exposure siding product, Western Red Cedar vertical-grain heartwood shingle, installed over oriented strand board (OSB) with a 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

7-26-11bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8140-2023:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** CEDAR VALLEY MANUFACTURING943 San Felipe Road, Hollister, CA 95023  
Contact: Jon Whorley (831) 636-8110 Fax (831) 636-8109  
Email: jonw@cedar-valley.com

**DESIGN:** Cedar Valley "California Stack" 1-Course Cedar Shingle Siding Panel, 4-1/4" or greater exposure, Western Red Cedar vertical-grain heartwood shingle applied over fiberglass mat to a square cut plywood backer, installed over oriented strand board (OSB) with a 7/16" minimum thickness. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

corrected 11-08-2011 jdd



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2023:0100 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CEDAR VALLEY MANUFACTURING943 San Felipe Road, Hollister, CA 95023  
Contact: Jon Whorley (831) 636-8110 Fax (831) 636-8109  
Email: jonw@cedar-valley.com

**DESIGN:** Cedar Valley Cedar-Lam 1 x 4 tongue & groove siding/paneling that has a 1/8" western red cedar veneer bonded to a 1/2" CDX plywood backer. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with SFM 12-7A-1 of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas. Width of panels may be greater than shown in the above Design section. Refer to listee's Installation Instruction Manual for details.

11-14-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2025:0006 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** COLLINS PRODUCTS, LLC6410 Highway 66, Klamath Falls, OR 97601  
Contact: Jeff Cronin (541) 885-3303 Fax (541) 885-3285  
Email: jcronin@collinsco.com

**DESIGN:** TruWood®7/16" Panel Siding, TruWood®1/2" Panel Siding, TruWood®7/16" Lap Siding, and TruWood®1/2" Lap Siding. All siding shall be installed over 5/8" Type X gypsum wallboard. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas when installed over 5/8" Type X gypsum wallboard.

02-06-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2026:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "Artisan®" lap siding, fiber-cement, 5/8" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2026:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "Gemplank®" lap siding, fiber-cement, 5/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

01-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2026:0003 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "Cempanel®" vertical siding, fiber-cement, 5/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.:** 8140-2026:0004 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "HardieShingleTM" panel, fiber-cement, 1/4" thick. "HardieShingleTM" lap siding, fiber-cement, 1/4" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Refer to manufacturer's installation instructions and product data sheets.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

01-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2026:0005 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "HardiePlank™" lap siding, fiber-cement, 5/16" thick. "HardiePanel™" vertical siding, fiber-cement, 5/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2027:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP SmartSide® Precision Series" exterior lap siding, oriented strand back-bone, 3/8" thick, applied over 1/2 standard gypsum wallboard. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2027:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP SmartSide® Precision Series" exterior panel siding, oriented strand back-bone, 7/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2027:0003 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP SmartSide® Foundation Series" exterior lap siding, wet process fiber back-bone, 1/2" thick, applied over 5/8" type X standard gypsum wallboard. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2027:0004 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP SmartSide® Foundation Series" exterior panel siding, wet process fiber back-bone, 7/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2027:0005 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP FlameBlock™" sheathing, 4' x 8' fire rated oriented strand board (OSB), 7/16" minimum nominal thickness with minimum Pyrotile thickness of 0.06, applied to fiberglass mat and Pyrotile laminate applied to one face of OSB, and SmartSide™ precision series lap siding cladding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and UL label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2027:0006 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

**DESIGN:** "LP FlameBlock™" sheathing, 4' x 8' fire rated oriented strand board (OSB), 7/16" minimum nominal thickness with minimum Pyrotile thickness of 0.06, applied direct to OSB sheathing and Pyrotile laminate applied to one face of OSB, and Cedar Sidewall Shingles, 1/2" butt end thickness cladding, or Plain Bevel solid wood siding, Cedar or other species, various widths. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and UL label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2029:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** NICHIIHA USA, INC. 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  
Contact: Ryuji Hotta (770) 805-9466 Fax (770) 805-9467  
Email: rhotta@nichiiha.com

**DESIGN:** EX Series "Field Stone" Brick and Stone panels siding, smooth and textured surfaces, 5/8" thick fiber cement, installed over 7/16" oriented strand board (OSB). Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

8-28-12 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2029:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** NICHIIHA USA, INC. 6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  
Contact: Ryuji Hotta (770) 805-9466 Fax (770) 805-9467  
Email: rhotta@nichiha.com

**DESIGN:** NichiFrontier, NichiStaggered and NishiStraight Shake panel siding, smooth and textured surfaces, 1/2" thick x 9" wide fiber cement, installed over 7/16" oriented strand board (OSB). Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

8-28-12 il



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2029:0003 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** NICHHA USA, INC.6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  
Contact: Ryuji Hotta (770) 805-9466 Fax (770) 805-9467  
Email: rhotta@nichha.com

**DESIGN:** NichiBoard smooth and cedar textures, unprimed cementitious board, 5-1/4", 6-1/4", 7-1/4", 8-1/4", 9-1/4" and 12' wide x 12 feet long x 5/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** correction made to remove reference to NFPA 72 on 05-01-14 gt

\*Correction 05-01-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2029:0004 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** NICHIIHA USA, INC.6659 Peachtree Industrial Blvd. Suite AA, Norcross, GA 30092  
Contact: Ryuji Hotta (770) 805-9466 Fax (770) 805-9467  
Email: rhotta@nichiha.com

**DESIGN:** NichiPanel smooth and cedar textures, unprimed cementitious panel, 4' x 8', 4' x 10', 4' x 12', and 5/16" thick. Refer to the manufacturer's installation instructions and product data sheets.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

08-28-12 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2031:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ROSEBURG FOREST PRODUCTS CO. PO Box 1088, Roseburg, OR 97470  
Contact: Dennis Cunningham (541) 464-7057 Fax (541) 874-3342  
Email: dennisc@rfpco.com

**DESIGN:** "Breckenridge" Siding, 19/32" thick \*with groove pattern of 3/8" wide, 1/4" deep and 4" oc.  
APA certified siding, installed over 15/32" CDX plywood sheathing or \*7/16" OSB or directly  
to studs. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances  
and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

\*Rev 05-01-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2031:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ROSEBURG FOREST PRODUCTS CO. PO Box 1088, Roseburg, OR 97470  
Contact: Dennis Cunningham (541) 464-7057 Fax (541) 874-3342  
Email: dennisc@rfpco.com

**DESIGN:** "Douglas Fir" siding, 19/32" thick, 12" groove spacing, 1.5" groove width, 3/8" groove depth, shiplap, APA certified siding, installed over 15/32" CDX plywood sheathing or \*directly to studs. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

\*Rev 09-04-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2031:0003 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ROSEBURG FOREST PRODUCTS CO. PO Box 1088, Roseburg, OR 97470  
Contact: Dennis Cunningham (541) 464-7057 Fax (541) 874-3342  
Email: dennisc@rfpco.com

**DESIGN:** "DuraTemp™" siding, 15/32" thick, 4 ply, 8" groove spacing, 3/8" groove width, lap edge, APA certified siding, installed over 15/32" CDX plywood sheathing. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

9-1-11 MT



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2031:0004 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** ROSEBURG FOREST PRODUCTS CO. PO Box 1088, Roseburg, OR 97470  
Contact: Dennis Cunningham (541) 464-7057 Fax (541) 874-3342  
Email: dennisc@rfpco.com

**DESIGN:** "DuraTemp™" siding, primed ship lap siding, 19/32" thick, 4'x8', 5 ply-4 plys Douglas fir veneer with hardboard face ply, 8" groove spacing, nominal 3/8" groove width, nominal 0.30" panel thickness at groove and lap edge (1/4" groove depth), APA certified siding indicating conformity with PRP- 108 and ICC-ES ESR-4856 evaluation report, installed over 1/2" plywood or 7/16" OSB sheathing or\*directly to studs. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

\*Rev 09-04-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2032:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SHAKERTOWN1200 Kerron Street, Winlock, WA 98596  
Contact: Mark Rutledge (360) 785-3501 Fax (360) 785-3076  
Email: mark@shakertown.com

**DESIGN:** "Shakertown® Craftman™" 1-course Cedar Shingle Panel siding, 4-1/2" thick or wider, manufactured using Western Red Cedar vertical-grain heartwood shingles over a full plywood back, 3/8" shingle butt and overlocking end-joints, and installed over 7/16" oriented strandboard (OSB) sheathing and #15 building paper. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2032:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SHAKERTOWN1200 Kerron Street, Winlock, WA 98596  
Contact: Mark Rutledge (360) 785-3501 Fax (360) 785-3076  
Email: mark@shakertown.com

**DESIGN:** Shakertown® Craftsman™ 1-Course Cedar Shingle Panel, 4-1/2", 7' and 14" exposure siding product, Western Red Cedar vertical-grain heartwood shingle, installed over oriented strand board (OSB) with a 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

05-19-11JD



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G V Joint & CV" siding CRA #17 Pattern Number 616 and 617, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0003 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G Butt Joint S2S" siding CRA #17 Pattern Number 633 and 634, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**

*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0004 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G Butt Joint S2S" siding CRA #17 Pattern Number 633EE and 634EE, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0005 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G V Joint S2S V 1 Side" siding CRA #17 Pattern Number 708, 715 and 716, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0006 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 708R, 715R and 716R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\* 10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0007 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G V Joint S2S V 1 Side" siding CRA #17 Pattern Number 711, 712 and 713, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0008 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "T&G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 726R, 727R and 728R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

LISTING No. 8140-2064:0012 Page 1 of 1

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

DESIGN: \*Nusku Fireblocker "Shiplap Butt JT" siding CRA #17 Pattern Number 761, 762 and 763, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only.

RATING: Compliance in accordance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as exterior siding for use in the Wildland Urban Interface areas.

NOTE: Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0013 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "1" Channel Shiplap" siding CRA #17 Pattern Number 774, 775 and 776, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

'10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0015 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "RAB R/Sawn Face" siding CRA #17 Pattern Number 391, 392, 393 and 394 Clear Fire Retardant Fingerjoint Redwood, minimum 3/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 II



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0016 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "RAB R/Sawn Face" siding CRA #17 Pattern Number 476, 477, 478 and 479 Clear Fire Retardant Fingerjoint Redwood, minimum 1 1/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0018 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "2 Lap" siding CRA #17 Pattern Number 433, Clear Fire Retardant Fingerjoint Redwood, minimum 1x10 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding installed in a horizontal orientatation only for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0019 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** \*Nusku Fireblocker "2 Lap" siding CRA #17 Pattern Number 431, Clear Fire Retardant Fingerjoint Redwood, minimum 1x8 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Product brand changed from Creatus Wood Premier™ to Nusku Fireblocker - 10-18-13.

\*10-18-13 ii



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires: **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0020 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "T&G V Joint REV R/Sawn Face" siding CRA #17 Pattern Number 711R, 712R and 713R, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaced 8140-2064:0001/Creatus Wood Products & 8140-2098:0001/California Timberline Inc - 10/18/13.

03-07-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
Fire Engineering Division



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0021 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "Channel Shiplap" siding CRA #17 Pattern Number 773, Clear Fire Retardant Fingerjoint Redwood, minimum 1x10 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaced 8140-2064:0010/Creatus Wood Products & 8140-2098:0002/CALIFORNIA TIMBERLINE INC. - 10/18/13.

3-7-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0022 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "Cove Shiplap" siding CRA #17 Pattern Number 770, 771 and 772, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaced 8140-2064:0009/CREATUS WOOD PRODUCTS & 8140-2098:0003/CALIFORNIA TIMBERLINE INC. - 10/18/13.

3-7-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2064:0023 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "V Joint Shiplap" siding CRA #17 Pattern Number 793, 794 and 795, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaces 8140-2064:0011/CREATUS WOOD PRODUCTS & 8140-2098:0004/CALIFORNIA TIMBERLINE INC. - 10/18/13.

3-7-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0024 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "RAB Smooth Face" siding CRA #17 Pattern Number 371, 372, and 373, Clear Fire Retardant Fingerjoint Redwood, minimum 3/4x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontal installation only. Refer to the manufacturer' installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaced 8140-2064:0014/CREATUS WOOD PRODUCTS and 8140-2098:0005/CALIFORNIA TIMBERLINE INC.- 10/18/13.

3-7-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2064:0025 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Nusku Partners LLC 4501 Brickell Privado Street, Ontario, CA 91761  
Contact: Tim Hummel (909) 974-0180 Fax (909) 974-0181  
Email: tim@nuskufireblocker.com

**DESIGN:** NuSku Fireblocker "2 Lap" siding CRA #17 Pattern Number 430, Clear Fire Retardant Fingerjoint Redwood, minimum 1x6 dimension, with no holes or knots, installed over oriented strand board (OSB) or plywood with 7/16" minimum thickness. For horizontally installation only. Refer to manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Listing replaced 8140-2064:0017/CREATUS WOOD PRODUCTS & 8140-2098:0006/CALIFORNIA TIMBERLINE INC.- 10/18/13.

3-7-12 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2070:0001 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** PLY GEM SIDING GROUP 2405 Campbell Road, Sidney, OH 45364  
Contact: Alan Hoying (937) 498-6720 Fax (937) 498-6127  
Email: alan.hoying@plygem.com

**DESIGN:** Model "Cedar Discovery" polypropylene siding panels. Panels are 64" x 14" with nominal thickness of 0.1". Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

10-05-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2070:0002 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** PLY GEM SIDING GROUP 2405 Campbell Road, Sidney, OH 45364  
Contact: Alan Hoying (937) 498-6720 Fax (937) 498-6127  
Email: alan.hoying@plygem.com

**DESIGN:** Model "Mastic Brentwood" PVC siding panels. Panels are 12' x 10" with nominal thickness of 0.04". Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

10-05-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8140-2070:0003 Page 1 of 1  
**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)  
**LISTEE:** PLY GEM SIDING GROUP 2405 Campbell Road, Sidney, OH 45364  
Contact: Alan Hoying (937) 498-6720 Fax (937) 498-6127  
Email: alan.hoying@plygem.com  
**DESIGN:** Model "Mastic Barkwood" PVC siding panels. Panels are 12' x 10" with nominal thickness of 0.048". Refer to the manufacturer's installation instructions and product data sheets.  
**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.  
**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.  
**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

10-05-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8140-2070:0004 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** PLY GEM SIDING GROUP 2405 Campbell Road, Sidney, OH 45364  
Contact: Alan Hoying (937) 498-6720 Fax (937) 498-6127  
Email: alan.hoying@plygem.com

**DESIGN:** Model Mastic Quest Vinyl Siding (Non-Weathered) is white PVC siding with dimensions of 144" x 10". Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

03-22-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2070:0005 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** PLY GEM SIDING GROUP 2405 Campbell Road, Sidney, OH 45364  
Contact: Alan Hoying (937) 498-6720 Fax (937) 498-6127  
Email: alan.hoying@plygem.com

**DESIGN:** Model Mastic Structure Vinyl Siding (Non-Weathered) is white insulated PVC siding with dimensions of 12'6"x12"x1 1/4". Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

03-22-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2085:0001 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS 1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0001

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2085:0003 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

11-23-11bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014** Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0003

11-23-11bh



---

This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2085:0004 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

XLF:

8140-2041:0004

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**

*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2085:0005 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

XLF: 8140-2041:0005

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

- LISTING No.** 8140-2085:0006 Page 1 of 2
- CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
- LISTEE:** CALIFORNIA REDWOOD COMPANY P.O. BOX, Arcata, CA 95518  
Contact: Kelly Lusa (707) 268-3096 Fax (707) 268-3089  
Email: klusa@calredwood.com
- DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
- Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.
- All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.
- RATING:** Compliance with Chapter 7A of the California Building Code.
- INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
- MARKING:** Listee name, Model number, rating and SFM label.
- APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

XLF: 8140-2041.0008

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2086:0001 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLFF:** 8140-2041:0001

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2086:0003 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0003

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2086:0004 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

XLF:

8140-2041:0004

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2086:0005 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**APPROVAL:** Compliance with Chapter 7A of the California Building Code.

**XLF:** 8140-2041:0005

i1-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2086:0006 Page 1 of 2

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** MENDOCINO FOREST PRODUCTS 1360 19th Hole Drive, Suite 200, Windsor, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoco.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0008

|1-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2089:0100 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** HUMBOLDT REDWOOD COMPANY/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA  
95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0001

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2089:0102 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** HUMBOLDT REDWOOD COMPANY/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

and in a manner acceptable to the authority having jurisdiction.

- MARKING:** Listee name, Model number, rating and SFM label.
- APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.
- XLFI:** 8140-2041:0003

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2089:0103 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** HUMBOLDT REDWOOD COMPANY/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0004

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2089:0104 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** HUMBOLDT REDWOOD COMPANY/C/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0005

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2089:0105 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** HUMBOLDT REDWOOD COMPANY/O 1360 19TH HOLE DRIVE #200, WINDSOR, CA 95492  
Contact: John Russell (707) 620-2977 Fax (707) 620-2964  
Email: jrussell@mendoc.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0008

12-22-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2091:0100 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SIERRA PACIFIC INDUSTRIES P O Box 496028, Redding, CA 96049  
Contact: Mark Pawlicki (530) 378-8000 Fax (530) 378-8499  
Email: mpawlicki@spi-ind.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**MARKING:** Listee name. Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0001

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2091:0102 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SIERRA PACIFIC INDUSTRIES P O Box 496028, Redding, CA 96049  
Contact: Mark Pawlicki (530) 378-8000 Fax (530) 378-8499  
Email: mpawlicki@spi-ind.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014** Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

**MARKING:** Listee name. Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0003

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2091:0103 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SIERRA PACIFIC INDUSTRIES P O Box 496028, Redding, CA 96049  
Contact: Mark Pawlicki (530) 378-8000 Fax (530) 378-8499  
Email: mpawlicki@spi-ind.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0004

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.:** 8140-2091:0104 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** SIERRA PACIFIC INDUSTRIES P O Box 496028, Redding, CA 96049  
Contact: Mark Pawlicki (530) 378-8000 Fax (530) 378-8499  
Email: mpawlicki@spi-ind.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0005

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2092:0100 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 652-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

12-20-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0001

12-20-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2092:0102 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 652-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

12-20-11 MFW



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0003

12-20-11 MFW



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2092:0103 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 852-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0004

12-20-11 MFW



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2092:0104 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 652-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLf:** 8140-2041:0005

12-20-11 MFW



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2092:0105 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** LAUSMANN LUMBER & MOULDING COP O BOX 65, LOOMIS, CA 95650  
Contact: Joe Lausmann (916) 652-9201 Fax (916) 652-4464  
Email: joe@lausmannlumber.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0008

12-21-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2094:0100 Page 1 of 2

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Unity Forest Products, Inc.P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

12-20-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0001

12-20-11 gt



---

This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

**Date Issued:** **July 01, 2014**

*Listing Expires* **June 30, 2015**

**Authorized By:** **JAMES PARSEGIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2094:0101 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

**LISTEE:** Unity Forest Products, Inc. P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0008

12-20-11 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2094:0102 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Unity Forest Products, Inc. P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances

1-10-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0003

i-10-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.:** 8140-2094:0104 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Unity Forest Products, Inc.P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0004

1-10-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2094:0105 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Unity Forest Products, Inc.P.O. Box 1849, Yuba City, CA 95992  
Contact: Enita Elphick (530) 671-7152 Fax (530) 671-7261  
Email: enita.elphick@unityforest.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0005

1-10-12 mfw



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2104:0002 Page 1 of 2

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Kubich Lumber11099 Mountaineer Trail, Grass Valley, CA 95945  
Contact: Tom Rowe (530) 272-8540  
Email: tmrowe@sbbmail.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Charnel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0003

03-28-12 gt



---

This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2104:0003 Page 1 of 2

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Kubich Lumber 11099 Mountaineer Trail, Grass Valley, CA 95945  
Contact: Tom Rowe (530) 272-8540  
Email: tmrowe@sbbmail.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



**MARKING:** Listee name, Model number, rating and SFM label.  
**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.  
**XLF:** 8140-2041:0001

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2104:0004 Page 1 of 1

**CATEGORY:** 8140 – EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Kubich Lumber11099 Mountaineer Trail, Grass Valley, CA 95945  
Contact: Tom Rowe (530) 272-8540  
Email: tmrowe@sbbmail.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0004

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2104:0005 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Kubich Lumber11099 Mountaineer Trail, Grass Valley, CA 95945  
Contact: Tom Rowe (530) 272-8540  
Email: tmrowe@sbbmail.com

**DESIGN:** Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas.

**XLF:** 8140-2041:0005

03-28-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2121:0100 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Pacific Wood Laminates, Inc. 885 Railroad Ave. PO Box 820, Brookings, OR 97415  
Contact: Chris Johnson (541) 469-4177 Fax (541) 469-6153  
Email: chrisj@socomi.com

**DESIGN:** "APA 303®" plywood siding with shiplap edges, nominal 19/32" thick (19/32 Performance Category) or greater and grooves spaced no closer than 4" on center or without grooves, and manufactured with veneers of all Southern Pine or Douglas Fir face, back and center with cross piles of PS1 Group 1 or 2 species, 4'x8' panel. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**NOTE:** Test Protocol SFM 12-7A-1

**XLFI:** 8140-2020:0001

01-08-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2121:0101 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Pacific Wood Laminates, Inc. 885 Railroad Ave. PO Box 820, Brookings, OR 97415  
Contact: Chris Johnson (541) 469-4177 Fax (541) 469-6153  
Email: chrisj@socomi.com

**DESIGN:** "APA 303®" plywood siding with reverse-board and batten, nominal 19/32" thick and shiplap edges, grooves spaced 12" on center, manufactured with face, back and center of Douglas Fir veneers and cross ply veneers of Hemlock or Douglas, 4'x8' panel. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

**XLF:** 8140-2020:0002

3-27-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2126:0100 Page 1 of 1  
**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)  
**LISTEE:** Blocks and Cutstock S.A.5065 Gold Creek Rd, Auburn, CA 95602 United States  
Contact: Richard Smallridge (916) 799-8404  
Email: pinebyr@suddenlink.net

**DESIGN:** Advantage Plus™ treated Radiata pine siding in the following patterns:

Profile	Nominal Size	Pattern Nos.
3/4" Rabbeted Bevel	3/4X6, 3/4X8, 3/4X10	371, 372, 373, 391, 392, 393
1-1/4" RAB	1-1/4X6, 1-1/4X8	476, 477
1" Drop (2 Lap & 3 Lap)	1X6, 1X8, 1X10	430, 431, 432, 433
1" V-rustic Shiplap	1X6, 1X8, 1X10	793, 794, 795
1" Cove, Square and Bevel Channel	1X6, 1X8, 1X10	770, 771, 772, 773(1X8, 1X10), 774, 775, 776
5/8" T&G	5/8X6, 5/8X8	205, 206
1" V&CV	1X6, 1X8	616, 617
1" T&G, T&G EE	1X6, 1X8	633, 634, 632EE, 633EE, 634EE
1" T&G 3/32"V/V2S	1X6, 1X8, 1X10	229, 230, 708, 715, 716, 708R, 715R, 716R
1" T&G 1/4"V	1X6, 1X8, 1X10	711, 712, 713

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for HORIZONTAL INSTALLATIONS ONLY for use in Wildland Urban Interface areas.

**NOTE:** Test Protocol 12-7A-1.

06-03-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014** Listing Expires **June 30, 2015**  
Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8140-2132-0100 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Arauco USA5901 B Peachtree Dunwoody RD NE, Ste 500, Atlanta, GA 30328  
Contact: Timothy Pruitt (770) 350-1647  
Email: tim.pruitt@arauco-usa.com

**DESIGN:** Arauco® TruChoice Treated Radiata pine siding with no through holes or loose knots, minimum nominal thickness of 3/4" and minimum nominal width of 6" and installed over oriented strand board with a minimum 7/16" thickness. For tongue and groove profile, minimum nominal thickness of 5/8" and minimum nominal width of 4". For horizontal installation only. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as solid wood sidings for use in the Wildland Urban Interface areas. For horizontal installation only.

**NOTE:** Test Protocol SFM 12-7A-1

08-06-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8140-2146:0100 Page 1 of 1

**CATEGORY:** 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** WATKINS SAWMILLSP O BOX 457, SUMAS, WA 98295  
Contact: Bill Hendricks (916) 698-6862 Fax (916) 372-9562  
Email: bill@saferbuilding.us

**DESIGN:** Watkins Certigrade red cedar shingles (18" Perfection) with 5-1/2" lap exposure, one layer of Typar \*House Wrap over Thermex\_FR fire-retardant treated exterior plywood (1/2"-ESR 1159). Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with CSFM 12-7A-1.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as exterior siding for use in the Wildland Urban Interface areas.

\*Rev 06-23-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

## 8150 – EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>CARRIAGE HOUSE DOOR COMPANY</b>	
<u>8150-2038:0001</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0002</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0003</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0004</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0005</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0006</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door. <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)
<u>8150-2038:0007</u>	<b>Company:</b> CARRIAGE HOUSE DOOR COMPANY <b>Address:</b> PO Box 572, West Sacramento, CA 95691 <b>Contact:</b> Doug Sequeira <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783 <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015 <b>Description:</b> Custom Wood Garage Door.

## 8150 – EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<u>8150-2038:0008</u>	<p><b>Company:</b> CARRIAGE HOUSE DOOR COMPANY  <b>Address:</b> PO Box 572, West Sacramento, CA 95691  <b>Contact:</b> Doug Sequeira  <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Custom Wood Garage Door.  <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8150-2038:0009</u>	<p><b>Company:</b> CARRIAGE HOUSE DOOR COMPANY  <b>Address:</b> PO Box 572, West Sacramento, CA 95691  <b>Contact:</b> Doug Sequeira  <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Custom Wood Garage Door.  <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8150-2038:0010</u>	<p><b>Company:</b> CARRIAGE HOUSE DOOR COMPANY  <b>Address:</b> PO Box 572, West Sacramento, CA 95691  <b>Contact:</b> Doug Sequeira  <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Custom Wood Garage Door.  <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<u>8150-2038:0011</u>	<p><b>Company:</b> CARRIAGE HOUSE DOOR COMPANY  <b>Address:</b> PO Box 572, West Sacramento, CA 95691  <b>Contact:</b> Doug Sequeira  <b>Phone:</b> (916) 446-1226 <b>Fax:</b> (916) 446-7783  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Custom Steel Garage Door.  <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Riviera Bronze Manufacturing</b>	
<u>8150-2120:0101</u>	<p><b>Company:</b> Riviera Bronze Manufacturing  <b>Address:</b> 1895 North Ventura Avenue, Ventura, CA 93001  <b>Contact:</b> Sid Anderson  <b>Phone:</b> (805) 653-1943 <b>Fax:</b> (805) 653-1942  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Metal glazed door assembly having a metal glazed window with structural silicone glazing and 1/4"(minimum) laminated annealed glass or insulated glass units with a minimum of one tempered pane.  <b>Category:</b> EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8150-2038:0001 Page 1 of 1

CATEGORY: 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: CARRIAGE HOUSE DOOR COMPANYPO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

DESIGN: Custom Wood Garage Door, constructed of 1/2" Douglas Fir plywood face covered with a 1/16" medium density fiberboard (MDF) veneer, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2" and measured 2-3/4" where the MDF moldings are affixed. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance in accordance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0002 Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 1/2" MDO (medium density overlay) plywood face covered with a 5/8" Extira trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2" and measured 2-3/4" where the Extira trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0003 Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 1/2" MDO (medium density overlay) plywood face covered with a 1/2" x 6 Clear Western Red Cedar 2nd layer, 1x6 Clear Western Red Cedar trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-3/4" and measured 3-1/16" where the Clear Western Red Cedar trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8150-2038:0004 Page 1 of 1

CATEGORY: 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

DESIGN: Custom Wood Garage Door, constructed of 1/2" MDO (medium density overlay) plywood face covered with 1x6 STK Incense Cedar trim, 1x6 STK Incense Cedar 2nd layer face, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-3/4" and measured 3-5/16" where the STK Incense Cedar trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance in accordance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires: **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0005 Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 5/8" MDO (medium density overlay) plywood face covered with a 5/8" Extira wood composite trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the 21 panel. The overall thickness of the door is 2-1/4" and measured 2-13/16" where the Extira trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8150-2038:0006

Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 1/2" MDO (medium density overlay) plywood face covered with 3/8" x 6 Mahogany overlay, 1x6 Mahogany trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-1/2" and measured 3-1/16" where the Mahogany trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8150-2038:0007 Page 1 of 1

CATEGORY: 8150 – EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: CARRIAGE HOUSE DOOR COMPANYPO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

DESIGN: Custom Wood Garage Door, constructed of ½" MDO (medium density overlay) plywood face covered with 1x6 Douglas Fir overlay, 1x6 Douglas Fir trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, ¼" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-3/4" and measured 3-5/16" where the Douglas Fir trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance in accordance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0008 Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANYPO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 1/2" MDO (medium density overlay) plywood face covered with 1x6 Redwood overlay, 1x6 Redwood trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-3/4" and measured 3-5/16" where the Redwood trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0009 Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANYPO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 5/8" Breckenridge siding face covered with 1x6 Clear Western Red Cedar trim, nominal 1-3/8" thick polystyrene foam 22 insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2-1/4" and measured 2-13/16" where the Clear Western Red Cedar trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

**LISTING No.** 8150-2038:0010

Page 1 of 1

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

**DESIGN:** Custom Wood Garage Door, constructed of 1/2" Marine Mahogany plywood face covered with 1x6 Clear Western Red Cedar or 1x6 Mahogany trim, nominal 1-3/8" thick polystyrene foam insulation occupying the hollow core, 1/4" plywood back face, and 1-3/8" thick by 2-1/2" wide Douglas Fir stiles and rails, with one stile located at the center of the panel. The overall thickness of the door is 2" and measured 2-11/16" where the Clear Western Red Cedar or Mahogany trim is affixed. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name. Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

Issued 7-21-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

**Date Issued:** July 01, 2014

*Listing Expires* June 30, 2015

**Authorized By:** JAMES PARSESIAN, Program Coordinator  
Fire Engineering Division

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8150-2038:0011 Page 1 of 1

CATEGORY: 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: CARRIAGE HOUSE DOOR COMPANY PO Box 572, West Sacramento, CA 95691  
Contact: Doug Sequeira (916) 446-1226 Fax (916) 446-7783  
Email: doug@carriagedoor.com

DESIGN: Custom Steel Garage Door constructed of 26 GA or thicker steel covering with 5 1/2" wood panel/rail (1/2" thick) around the perimeter and down the vertical center. Core filled with polystyrene insulation. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance in accordance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and SFM label.

APPROVAL: Listed as an Exterior Door Assembly for use in the Wildland Urban Interface areas.

NOTE: Test Protocol SFM 12-7A-1.

02-11-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



Page 1 of 1

**LISTING No.** 8150-2120:0101

**CATEGORY:** 8150 -- EXTERIOR DOOR FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Riviera Bronze Manufacturing 1895 North Ventura Avenue, Ventura, CA 93001  
Contact: Sid Anderson (805) 653-1943 Fax (805) 653-1942  
Email: sea@rivierabronze.com

**DESIGN:** Metal glazed door assembly having a metal glazed window with structural silicone glazing and 1/4"(minimum) laminated annealed glass\*or insulated glass units with a minimum of one tempered pane. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Compliance in accordance with Chapter 7A of the California Building Code.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as an Exterior metal door with glazing for use in the Wildland Urban Interface areas.

\*Rev 04-03-13 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*

## 8160 – UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

Listing Number	Listing Information
<b>JAMES HARDIE BUILDING PRODUCTS, INC.</b>	
8160-2026:0006	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "CemSoffit@" un-vented, fiber-cement soffit, 3/16" thick and ¼" thick under eave material.  <b>Category:</b> UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
8160-2026:0007	<p><b>Company:</b> JAMES HARDIE BUILDING PRODUCTS, INC.  <b>Address:</b> 10901 Elm Avenue, Fontana, CA 92337  <b>Contact:</b> Chad Diercks  <b>Phone:</b> (909) 356-6366 <b>Fax:</b> (909) 427-0634  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "HardieSoffit@" un-vented, under eave material.  <b>Category:</b> UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>LOUISIANA-PACIFIC</b>	
8160-2027:0007	<p><b>Company:</b> LOUISIANA-PACIFIC  <b>Address:</b> 414 Union Street, Suite 2000, Nashville, TN 37219  <b>Contact:</b> Rex Swanson  <b>Phone:</b> (480) 352-3667  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> "LP FlameBlock™" sheathing.  <b>Category:</b> UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Woodtone Building Products</b>	
8160-2115:0100	<p><b>Company:</b> Woodtone Building Products  <b>Address:</b> 8007 Aitken Road, Chilliwack, BC V2R-4H5 Canada  <b>Contact:</b> Mike Pidlisecky  <b>Phone:</b> 604-792-3680 <b>Fax:</b> 604-792-3930  <b>Date Issued:</b> 07/01/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Model FireGuard™ engineered wood trim product nominal 1" x 8" for both exterior and interior applications.  <b>Category:</b> UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)</p>
<b>Boral Composites Inc.</b>	
8160-2134:0104	<p><b>Company:</b> Boral Composites Inc.  <b>Address:</b> 200 Mansell Court East, Suite 305, Roswell, GA 30076  <b>Contact:</b> Guy Crocco  <b>Phone:</b> (210) 332-8394 <b>Fax:</b> (770) 645-2888  <b>Date Issued:</b> 07/03/2014 <b>Listing Expires:</b> 06/30/2015  <b>Description:</b> Boral TruExterior® Trim 1-1/2" actual thickness in widths 3-1/2" to 11-1/4" actual dimensions.  <b>Category:</b> UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)</p>

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8160-2026-0006 Page 1 of 1

**CATEGORY:** 8160 -- UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "CemSoffit®" un-vented, fiber-cement soffit, 3/16" thick and 1/4" thick, under eave material.  
Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Non combustible

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances  
and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as under eave materials for use in the Wildland Urban Interface areas.

Issued 06-18-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSESIAN, Program Coordinator**  
*Fire Engineering Division*



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8160-2026:0007 Page 1 of 1

**CATEGORY:** 8160 -- UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** JAMES HARDIE BUILDING PRODUCTS, INC. 10901 Elm Avenue, Fontana, CA 92337  
Contact: Chad Diercks (909) 356-6366 Fax (909) 427-0634  
Email: chad.diercks@jameshardie.com

**DESIGN:** "HardieSoffit®" un-vented, fiber-cement soffit, 3/16" thick and ¼" thick, under eave material.  
Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** Non Combustible

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances  
and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as under eave materials for use in the Wildland Urban Interface areas.

Issued 06-18-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN**, Program Coordinator  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



## LISTING SERVICE

LISTING No. 8160-2027:0007 Page 1 of 1

CATEGORY: 8160 -- UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

LISTEE: LOUISIANA-PACIFIC 414 Union Street, Suite 2000, Nashville, TN 37219  
Contact: Rex Swanson (480) 352-3667  
Email: Rex.Swanson@lpcorp.com

DESIGN: "LP FlameBlock™" sheathing, 4' x 8' fire rated oriented strand board (OSB), 15/32" minimum nominal thickness with minimum Pyrotile applied direct to one face of OSB, 1/8" gap at joist nailer and Cedar and Redwood v-ceiling cladding products of nominal 5/8" (thickness or greater) x 4" (Width or wider). Refer to the manufacturer's installation instructions and product data sheets.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name, Model number, rating and UL label.

APPROVAL: Listed as under eave materials for use in the Wildland Urban Interface areas.

09-12-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGIAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 8160-2115:0100 Page 1 of 1

**CATEGORY:** 8160 – UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Woodtone Building Products 8007 Aitken Road, Chilliwack, BC V2R-4H5 Canada  
Contact: Mike Pidlisecky 604-792-3680 Fax 604-792-3930  
Email: mike@woodtone.com

**DESIGN:** Model FireGuard™ engineered wood trim product nominal 1" x 8" for both exterior and interior applications. Refer to the manufacturer's installation instructions and product data sheets.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and Intertek label.

**APPROVAL:** Listed as under eave materials for use in the Wildland Urban Interface areas.

12-18-12 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2014**

Listing Expires **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM  
**LISTING SERVICE**



**LISTING No.** 8160-2134:0104 Page 1 of 1

**CATEGORY:** 8160 -- UNDER EAVE FOR WILDLAND URBAN INTERFACE (W.U.I)

**LISTEE:** Boral Composites Inc. 200 Mansell Court East, Suite 305, Roswell, GA 30076  
Contact: Guy Crocco (210) 332-8394 Fax (770) 645-2888  
Email: [guy.crocco@boral.com](mailto:guy.crocco@boral.com)

**DESIGN:** Boral TruExterior® Trim 1-1/2" actual thickness in widths 3-1/2" to 11-1/4" actual dimensions. Refer to the manufacturer's installation instructions and product data sheets.

**RATING:** SFM 12-7A-3

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee name, Model number, rating and SFM label.

**APPROVAL:** Listed as under eave materials for use in the Wildland Urban Interface areas. Refer to manufacturer's Installation Manual for details.

07-01-14 gt



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 03, 2014**

*Listing Expires* **June 30, 2015**

Authorized By: **JAMES PARSEGAN, Program Coordinator**  
*Fire Engineering Division*

**8180 – NON-WOOD ROOF COVERING/ASSEMBLIES FOR WILDLAND URBAN INTERFACE (W.U.I)**

**NO LISTINGS**